

1-5 ton G Series
AC ELECTRIC PLATFORM TRUCK



HELI
LIFTING THE FUTURE



1-5ton


AC ELECTRIC PLATFORM TRUCK



»» Brief Introduction

As the newly designed environmentally friendly tractor machines, **HELI G series 1-5T AC Electric Platform Truck** has the unique profiling, ergonomically and aesthetic philosophy combination for operator comfort and ease of use, maintenance convenience.

This machine is powered by battery, with World-famous Curtis AC controller matched AC motors to supply the stepless accelerating, high efficiency, reliable quality, comfortable operation, and strong power.




Drive system

- Special drive axle for electric machines with low noise, non-pollution, stable running, perfect sealing, and also with enough ground clearance for good trafficability.
- Large gear ratio, powerful traction, strong gradeability, perfect performance, suitable for complex operating condition.

Steering system


- With fully-hydraulic Transverse cylinder power steering or circulating ball type redirector, easily steering, and long working life.
- Front and rear suspension are with elastic connection for more comfort.



Optional Equipment——Cabin



Optional Equipment—— Platform guard bar



Superior intelligent design


- Intelligent components and function for the better safety to driver and machines, also supply the higher working efficiency, and reduce the energy-consumption.

Operating system

- Comfortable brake/accelerating pedal position with light stepping strength, fully meeting ergonomically demands.
- With front-rear adjustable steering wheel to satisfy different height drivers.
With excellent cold-brake efficiency, enough brake force, fully meet the parking and driving brake standard.

Chassis system



- Side-extraction battery replace, very convenient and reliable.






1-5ton


AC ELECTRIC PLATFORM TRUCK



>> Interactive Multifunctional Display



>> Optional auto water-filling battery (Optional)



>> Energy regeneration

- Energy regeneration with AC technology control for the energy-saving, the single shift working time of the battery is increased by 15%

↑15% THE SINGLE SHIFT WORKING TIME OF THE BATTERY IS INCREASED BY

- Reliable multifunctional display showing working condition, fault detection information for more direct and convenient reading.

Technical Parameters

Item		unit	G series 1-5t AC Electric Platform Truck						
1 Truck Model			BD10-JB1	BD20-JA1	BD20-JB1	BD30-JA1	BD30-JB1	BD40-JA1	BD50-JA1
2 Operating mode			Seated						
3 Capacity		t	1	2	2	3	3	4	5
4 Wheelbase		mm	1150	1650	1650	1650	1650	1810	2100
5 Weight		kg	880	1500	1500	1500	1500	2200	2400
6 front-rear tires load without load		kg	440/440	800/700	800/700	800/700	800/700	1000/1200	1150/1250
7	Type		Pneumatic tires						
8 Tires	Front tire		5.00-8	6.50-10	6.50-10	6.50-10	6.50-10	7.00-12	7.00-12
9	Rear tire		5.00-8	6.50-10	6.50-10	6.50-10	6.50-10	7.00-12	7.00-12
10 Seat height(front ground)		mm	735	860	860	860	860	980	980
11 Traction base height		mm	450(Optional)	580(Optional)	580(Optional)	580(Optional)	580(Optional)	720(Optional)	720(Optional)
12 Truck dimension(length*width*height)		mm	2750×1000×1225	3615×1400×1400	3615×1400×1400	3615×1400×1400	3615×1400×1400	3970×1500×1500	4575×1500×1500
13 Platform dimension(length*width*height)		mm	1400×1000×560	2240×1400×680	2240×1400×680	2240×1400×680	2240×1400×680	2600×1500×850	3200×1500×850
14 Min. Ground clearance		mm	80	130	130	130	130	120	120
15 Turning radius		mm	3000	3100	4300	3100	4300	4400	4600
16 Driving speed(without/load)		km/h	8.0/10.0	12.0/16.0	12.0/16.0	12.0/16.0	12.0/16.0	12.0/15.0	12.0/15.0
17 Gradeability(with load)		%xm	10%x20m	10%x20m	10%x20m	10%x20m	10%x20m	10%x20m	8%x20m
18 Driving brake			Hydraulic brake and electric brake						
19 Parking brake			Mechanic						
20 Driving mode			Rear drive						
21 Drive motor rated power		kw	3	4	4	5	5	6	6
22 Steering motor rated power		kw	/	1.35	/	1.35	/	1.35	1.35
23 Battery/rated capacity(5H)		V/Ah	24/280	48/280	48/280	48/280	48/280	48/350	48/450
24 Battery weight		kg	300	550	550	550	550	579	715
25 Tread, front tire		mm	790	1160				1250	
26 Tread, rear tire		mm	820	1160				1250	
27 Driving control mode			Electronic stepless mode						
28 Operator's ear noise		db(A)	<65						
29 Controller type			CURTIS AC controller						

Standard configuration

Streamlined glass fiber cover	Took kits
Battery	
Liquid crystal combination display	
Pneumatic tires	
Traction pin	

Optional configuration

Cabin	Different height traction pin
Platform guard bar	Solid tire
Beacon	Simple rain cover
Crate	Optional paint color
Optional dimension platform	Immotion controller



检测 CNAS L7096

HELI CANADA

5705, place Kubota
Drummondville (Qc)
Canada, J2B 6V4
1-833-HELICAN
info@heliforklift.ca
heliforklift.ca



Our products are subject to improvements and changes without notice.